



JACO MANUFACTURING, INC.  
Mountain Empire Industrial Park  
P. O. BOX 550 ATKINS, VA 24311  
Ph: (877) 660-2688 Ph: (276) 783-2688  
Fax: (276) 783-4222  
Email: [jaco@jacomanufacturing.com](mailto:jaco@jacomanufacturing.com)  
Web: [www.jacomanufacturing.com](http://www.jacomanufacturing.com)

## DRAFT SEALER™

### PRODUCT DATA SHEET

#### DESCRIPTION:

**DRAFT SEALER™ IS A SUPERIOR FIRESTOPPING CAULK SPECIFICALLY FORMULATED TO SEAL UNWANTED DRAFTS AND VOIDS AROUND FRAMING, MASONRY, AND UTILITY SERVICE PENETRATIONS. DRAFT SEALER™ HAS EXCELLENT ACOUSTICAL INSULATING PROPERTIES.**

SPECIFIC GRAVITY 1.31  
WITHSTANDS 2000°F (1093°C)

Ph: NEAR NEUTRAL  
COLOR: LIGHT RED

#### COMPLIANCE:

**DRAFT SEALER™ COMPLIES TO THE ASTM-E136 STANDARD, IS RATED ZERO FLAME SPREAD / ZERO SMOKE DEVELOPED PER ASTM-E84, WITHSTANDS 2000°F FOR 4 HOURS, AND MEETS THE NON-COMBUSTIBLE REQUIREMENTS OF BOCA, CABO, MEC, SBC, UBC AND MOST OTHER BUILDING CODES.**

#### LIMITATIONS:

**DRAFT SEALER™ SHOULD NOT BE APPLIED WHEN THE TEMPERATURE IS BELOW FREEZING, IN CONTINUOUSLY WET AREAS, OR IN EXPANSION JOINTS. BUILDING CODES VARY TO ACCOMMODATE GEOGRAPHY AND THE INTENDED USE OF THE STRUCTURE. APPROVED USE OF ANY PRODUCT IS THE SOLE RESPONSIBILITY OF THE CODE ENFORCEMENT AGENCY.**

#### APPLICATION:

**DRAFT SEALER™ CAN BE EASILY APPLIED WITH A CAULK GUN OR TROWEL. THE NON-SAGGING QUALITY OF THIS PRODUCT PROVIDES A COST EFFECTIVE MEANS OF SEALING AROUND HVAC DUCTS, MASONRY, PLUMBING AND WIRING PENETRATIONS, AND MOST OTHER INTERIOR CONSTRUCTION VOIDS. WHEN FILLING VOIDS LARGER THAN ONE INCH, MINERAL WOOL OR OTHER NON-COMBUSTIBLE MATERIAL CAN BE ADDED AS SUPPORTING FILLER.**

#### WARRANTY:

**DRAFT SEALER™ IS GUARANTEED TO COMPLY TO ASTM-E136-96a, AND REMAIN STABLE FOR THE LIFE OF THE FIXED STRUCTURE. THIS GUARANTEE IS LIMITED TO THE PURCHASE PRICE. NO OTHER GUARANTEE OR WARRANTY IS OFFERED OR IMPLIED.**

#### STORAGE AND HANDLING:

**DRAFT SEALER™ IS A WATER BASED FORMULA OF INERT INGREDIENTS WITH EXCELLENT PACKAGE LIFE. UNOPENED CONTAINERS ARE NOT AFFECTED BY FREEZE/THAW CYCLES OR SEASONAL STORAGE UP TO 160 F. THIS NON-STAINING, NON-TOXIC CAULK CAN BE REMOVED WITH SOAP AND WATER AND IS ENVIRONMENTALLY SAFE.**

#### AVAILABILITY:

**DRAFT SEALER™ IS SUPPLIED IN STANDARD 10.5 FL. OZ, QUART TUBE, AND BULK CONTAINERS.**